



Premier Elite SmartKey

Ricochet® enabled keyfob

- Remote arm, part arm and disarm
- Integral RFID proximity tag for use with compatible prox readers
- Alarm system status display
- Programmable two button panic alarm
- Remote control of up to 3 programmable outputs. Typical applications include garage door control, external lighting control and automatic gate control
- Replaceable lithium CR2 battery offers 2 to 3 year typical battery life
- PD 6662: 2010, EN 50131-1, EN 50131-3, EN 50131-5-3 Grade 2 Class II

Premier Elite CO-W

Ricochet enabled carbon monoxide detector

- Continually monitoring CO sensor
- Compatible with Premier Elite control panels
- 10 year sensor lifespan
- 4 year typical battery life (2 x 1.5V AA Alkaline, included)
- EN 50131-1, EN 50131-5-3 Grade 2 Class II
- EN 50291-1 Approved



Premier Elite OH-W

Ricochet enabled optical heat fire detector

- Optical and heat fire sensing
- 85dB(A) built-in sounder
- Powered by 3 x AAA batteries (included)
- 1.5 year battery life

Premier Elite PA DP-W

Ricochet enabled double push panic button

- Silent operation
- Up to 4 year battery life
- 'ACPO 10 Point Plan' compliant



Texecom products are designed and manufactured in the UK

www.texecom.com

sales@texecom.com



Micro Contact-W

Miniature wireless contact with *Ricochet* Mesh Technology

- Small size: 57mm x 27.5mm x 8.2mm
- Compatible with Premier Elite control panels, Premier control panels & *Ricochet* Expansion Packs
- LED assisted setup procedure
- Adhesive or screw fixing options
- 4-Year typical battery life
- Three colour options
- EN50131-2-6 Grade 2
- Cost effective



Premier Elite Impaq Plus-W

Ricochet enabled shock sensor

- Includes optional magnetic contact
- Typical 2 to 3 year battery life
- Suitable for commercial applications
- PD 6662:2010 Grade 2 Class II

Premier Elite Impaq Contact-W

Ricochet enabled magnetic contact

- Includes 2 optional hard wired inputs
- Typical 2 to 3 year battery life
- Suitable for commercial applications
- PD 6662:2010 Grade 2 Class II

